



Dehumidification Application

The choice for
desiccant dehumidification®

® and ™ Trademarks of Bry-Air (Asia) Pvt. Ltd.

CORROSION PREVENTION

Bry-Air environmental control systems prevent the damaging effects of corrosion due to the formation of condensation.

In general, it is safe to assume that most materials, particularly ferrous metals, are subject to corrosion. By this we mean that every substance eventually changes from one form to another as a result of chemical reactions. Many of these reactions, particularly those which depend upon oxygen, are catalyzed and accelerated by moisture.

Ferrous metals, such as iron and steel, are well known for their corrosion in the presence of moisture. Less well known is the fact that glass corrodes and cracks at a rate which varies according to the moisture on its surface. Pure crystals, such as sodium iodide and

lithium fluoride can also corrode, forming oxides and hydroxides in proportion to the moist air. Non-ferrous metals such as copper are more sensitive to corrosion than plates of ferrous metals.

In corrosion prevention applications, the controlled space is maintained at a specific relative humidity and temperature so that the products or material in the controlled space cannot adsorb moisture from the surrounding atmosphere. Thus the products are also protected from

corrosion. As a general rule, rust and other oxidizing type corrosion reactions will not occur if the relative humidity in the area is maintained at or below 40% R.H. Materials or product residing in this atmosphere need not be coated with oil or other surface protection, and can thus be kept in ready-to-use condition.

Some of the corrosion prevention applications do not have coincidental temperature control. Humidity control is maintained to achieve protection of the area or products in the area, as this constitutes a much more economical method than air conditioning. An example of this is a waste pumping station or sewage plant, where the primary humidity control problem is the maintenance of a dew point within the space which is lower than the temperature of the liquid that is being circulated or stored there. In this way, condensation of moisture on the outside of pumps and piping is eliminated, thus significantly reducing the cost of painting and component cost due to corrosion.



Photo Courtesy of MCT Direct Photos



Photo Courtesy of MCT Direct Photos


The world's economies are beginning to depend more and more on light equipment such as computers, high energy batteries and sophisticated telecommunication cabling. While these are less subject to gross rusting, they are very sensitive to microscopic - level corrosion. The fact that these circuits consist of very little material to begin with, means that small amounts of corrosion create disproportionately larger problems. Circuits utilizing electrical contacts made of copper alloys are more susceptible to corrosion

In the past 40 years, Bry-Air Desiccant Dehumidifiers have saved our customers millions of dollars each year by preventing corrosion on both a gross and microscopic basis.

Corrosion application areas would include the following:

- Precision Tooling Storage
- Nuclear Waste Storage
- Ammunition Storage
- Tire Creel Rooms
- Razor Blade Manufacturing
- Tritium Containment
- Marine Drilling Rig Lay-ups
- Water Pumping Stations
- Sewage and Wastewater Treatment Plants
- Industrial Plant Lay-ups
- Turbine Lay-ups
- Electrical Cabling and Wiring
- Galvanized Steel Storage
- Protecting Box Beams in Bridges
- Oil Tanker and Ship Lay-ups
- Ball Bearing Storage
- SCR Motor Control Centers
- Sodium Iodide Crystal Finishing
- Military Aircraft Avionics Protection
- Civil Aircraft Corrosion Protection
- Military Tanks
- Helicopter Storage
- Metal Hydride Machining
- Calcium metal Fabrication
- Chemical Plant Pipe Galleries
- Computer Storage
- Electrical Circuit Boards

Typical Rate of Corrosion for Ferrous Metals



For more information on Bry-Air's products and services please visit www.bry-air.com

Bry-Air, Inc. - 10793 St. Rt. 37 W. Sunbury, Ohio 43074 - P: 740.965.2974 - F: 740.965.5470 - E: bryair1@bry-air.com